

ON/OFF

TIRES DESIGNED TO PROVIDE OUTSTANDING TRACTION ON UNPAVED SURFACES, MUD, SAND, GRAVEL AND ON EVERY TERRAIN. EXTREME DEEP TREAD PATTERN WITH WIDE GROOVES TO MOVE FORWARD AND OVERCOME EVERY OBSTACLE IN THE ROUGHEST WORKING CONDITIONS. ROBUST AND CONSOLIDATED TECHNICAL SOLUTIONS ARE USED IN TREAD AND CASING COMPONENTS TO ASSURE SOLID AND RELIABLE PRODUCTS FOR THE HEAVIEST APPLICATIONS. PREMIUM QUALITY MATERIALS ARE SELECTED TO ACHIEVE A SUPERIOR COMPOUND REINFORCEMENT FOR AN ENHANCED MILEAGE AND IMPROVED RESISTANCE TO CUTS AND TEARING IN TREAD AND SIDEWALL AREAS.

CORPORATE SOCIAL RESPONSIBILITIES

MISSION & COMMITMENT

Giti Tire endorses the United Nations Sustainable Development Goals (SDGs) and incorporates them into each CSR activity. These goals cover a broad range of social and economic development issues. Included among them are poverty, hunger, health, education, climate change, gender equality, water sanitation, energy, environment, and social justice.



ON/OFF



Enjoy Driving



GAO897



OFF-ROAD TIRE FOR HIGH-MOBILITY VEHICLES UNDER ALL ROAD CONDITIONS

- > Designed to work with a wide range of air pressures, to optimise performance in different road conditions
- > Very applicable in temperatures ranging from a maximum of 55 °C to minimum -40 °C
- > High-stability tread with maximised mileage




FEATURES

BENEFITS



Robust blocks and wide longitudinal grooves in combination with extra-deep pattern design

Provides excellent traction and superior stability to climb over every obstacle even in the roughest working terrains



Reinforced tread compound with advanced anti-cut properties and high abrasion resistance

High resistance against tread chunking and tearing on aggressive terrains and extremely high mileage when used on asphalt roads



Optimised tire construction parameters and consolidated technical solutions

High working application flexibility in every environment, including different pressure settings and temperature ranges



Optimised bead contour design

Easy fitting on the rim and enhanced endurance in low pressure running conditions

| Size | LI | SI | Pattern | | Rim | Load Single Kg | Load Dual Kg | | | Noise dB | | | |
|----------|---------|----|---------|--|------|----------------|--------------|-----|------|----------|---|---|---|
| 14.00R20 | 164/161 | J | GAO897 | | 10.0 | 5000 | 4625 | 375 | 1253 | * | * | * | * |

* Excluded from EU labelling (POR tire)