

URBAN



Size	LI	SI	Tube Type	Pattern	Noise (dB)	A	B	C	D
245/70R19.5	136/134	M	TL	GT867	3PMSF	70	A	B	E
11R22.5	148/145	J	TL	GT867	3PMSF	71	A	C	D
305/70R22.5	152/150 (154/150)	J (E)	TL	GT867	M+S	72	A	C	D
315/80R22.5	158/150	J	TL	GT867	M+S	72	A	C	C
215/75R17.5	128/126	M	TL	GAU867 ^{V1}	3PMSF	70	A	C	D
265/70R19.5	143/141	J	TL	GAU867 ^{V1}	3PMSF	70	A	C	D
11R22.5	148/145	J	TL	GAU867 ^{V1}	3PMSF	71	A	C	D
275/70R22.5	152/148 (154/148)	J (F)	TL	GAU867 ^{V1}	3PMSF	70	A	C	C
295/80R22.5	154/150	J	TL	GAU867 ^{V1}	3PMSF	71	A	C	D

WINTER



Size	LI	SI	Tube Type	Pattern	Noise (dB)	A	B	C	D
315/70R22.5	156/150 (154/150)	L (M)	TL	GSW226	3PMSF	72	B	C	D
315/80R22.5	158/150 (154/150)	L (M)	TL	GSW226	3PMSF	72	B	C	D
385/55R22.5	158 (160)	L (J)	TL	GSW226	3PMSF	73	B	B	D
385/65R22.5	164 (160)	K (L)	TL	GSW226	3PMSF	72	B	B	D
315/70R22.5	154/150 (152/148)	L (M)	TL	GDR621+	3PMSF	75	B	B	D
315/80R22.5	158/150 (154/150)	L (M)	TL	GDR621+	3PMSF	75	B	B	D

APPLICATION


- COMBI ROAD**
- > Combines regional haul and long haul benefits
 - > Gives flexibility in a variety of applications



- LONG HAUL**
- > Long distance journeys mainly on motorways and trunk roads
 - > Constant speeds with minimal braking and accelerating



- REGIONAL**
- > Shorter journeys on regional national roads
 - > Flexible in a variety of applications
 - > Frequent braking, acceleration and turning



- MIXED SERVICE**
- > Frequent use both on and off road
 - > Higher loads
 - > Increased risk of damage from road conditions



- ON/OFF**
- > High mobility under all conditions in off road application



- URBAN**
- > Constant stop and go operating conditions
 - > Frequent speed changes and turning
 - > Increased risk of damage from curbing impacts



- WINTER**
- > 3PMSF winter performance requirement
 - > High traction in snow, ice and wet road conditions



Tire Range

Truck and Bus

Enjoy Driving

The information contained in this catalogue is for general information purposes only. Every effort has been made to ensure the product information provided is accurate and up to date at the time of going to press. We reserve the right to make changes to the product range, descriptions, markings and make modifications or substitutions without prior notice.

Version 22.1 EU



CORPORATE SOCIAL RESPONSIBILITIES

MISSION & COMMITMENT


Giti Tire endorses the United Nations Sustainable Development Goals (SDGs) and incorporates them into each CSR activity. These goals cover a broad range of social and economic development issues. Included among them are poverty, hunger, health, education, climate change, gender equality, water sanitation, energy, environment, and social justice.



SUSTAINABLE DEVELOPMENT GOALS




REDUCE
Thanks to our design approach, our tires are lighter, consume less energy and last longer.



REUSE
Our tires are repairable, regroovable, retreadable.



RENEW
We use eco_design materials from renewable resources.



RECYCLE
We incorporate recycled materials into our new tires.



GPSNR MEMBERSHIP



You can learn more about Giti's environmental and other sustainable efforts at



UNGC MEMBERSHIP



Further details about the United Nations Global Compact can be seen on their website here

COMBI ROAD



Size	LI	SI	Tube Type	Pattern	Noise (dB)	A	B	C	D
215/75R17.5	128/126	M	TL	GSR236	3PMSF	67	A	B	D
295/80R22.5	154/149	M	TL	GSR237	3PMSF	70	A	B	C
315/70R22.5	156/150 (154/150)	L (M)	TL	GSR237	3PMSF	70	A	B	C
355/50R22.5	156	L	TL	GSR237	3PMSF	70	A	B	B
245/70R19.5	136/134	M	TL	GSR225	3PMSF	71	A	C	C
265/70R19.5	140/138	M	TL	GSR225	3PMSF	71	A	C	D
285/70R19.5	146/145	M	TL	GSR225	3PMSF	71	A	C	C
11R22.5	148/145	M	TL	GSR225	3PMSF	71	A	C	D
12R22.5	152/149	L	TL	GSR225	3PMSF	71	A	C	D
275/70R22.5	148/145 (152/148)	M (J)	TL	GSR225	3PMSF	71	A	C	C
295/80R22.5	154/149	M	TL	GSR225	3PMSF	72	B	B	D
295/60R22.5	150/147	L	TL	GSR225	3PMSF	71	A	B	C
315/60R22.5	154/148	L	TL	GSR225	3PMSF	71	A	C	C
315/70R22.5	156/150 (154/150)	L (M)	TL	GSR225	3PMSF	71	A	B	C
315/80R22.5	158/150 (154/150)	L (M)	TL	GSR225	3PMSF	71	A	B	C
385/55R22.5	158 (160)	L (K)	TL	GSR259	3PMSF	70	A	B	C
385/65R22.5	164(160)	K (L)	TL	GSR259	3PMSF	70	A	B	C
295/80R22.5	152/149	M	TL	GDR675	3PMSF	71	A	B	D
315/60R22.5	152/148	L	TL	GDR675	3PMSF	71	A	B	D
315/70R22.5	154/150 (152/148)	L (M)	TL	GDR675	3PMSF	71	A	B	D
315/80R22.5	156/150 (154/150)	L (M)	TL	GDR675	3PMSF	71	A	B	D
315/70R22.5	154/150 (152/148)	L (M)	TL	GDR655+	3PMSF	74	B	C	D
315/80R22.5	156/150 (154/150)	L (M)	TL	GDR655+	3PMSF	74	B	C	D
11R22.5	148/145	M	TL	GDR655	3PMSF	74	B	C	E
295/80R22.5	152/149	M	TL	GDR655	3PMSF	74	B	C	D
295/80R22.5	152/149	M	TL	GDR665+	3PMSF	76	B	C	D
315/80R22.5	156/150 (154/150)	L (M)	TL	GDR665	3PMSF	76	B	B	D
215/75R17.5	136/134	K	TL	GTR955	3PMSF	66	A	B	C
235/75R17.5	143/141 (146/146)	K (F)	TL	GTR955	3PMSF	67	A	B	C
245/70R17.5	143/141 (146/146)	K (F)	TL	GTR955	3PMSF	67	A	B	C
385/55R22.5	160 (158)	K (L)	TL	GTR955	3PMSF	69	A	B	B
385/65R22.5	164 (158)	K (L)	TL	GTR955	3PMSF	71	A	B	B

LONG HAUL



Size	LI	SI	Tube Type	Pattern	Noise (dB)	A	B	C	D
10R22.5	144/142	M	TL	GAL817		70	A	C	D
255/70R22.5	140/137	M	TL	GAL817		70	A	C	C
295/60R22.5	150/147 (149/146)	K (L)	TL	GDL617	3PMSF	74	B	C	D
295/80R22.5	152/148	M	TL	GDL617	3PMSF	74	B	C	C
315/60R22.5	152/148	L	TL	GDL617	3PMSF	74	B	B	D
315/70R22.5	154/150 (152/148)	L (M)	TL	GDL617	3PMSF	74	B	C	D
315/80R22.5	156/150 (154/150)	L (M)	TL	GDL617	3PMSF	74	B	C	D
215/75R17.5	136/134	J	TL	GTL919	3PMSF	69	A	C	D
235/75R17.5	143/141 (146/146)	J (F)	TL	GTL919	3PMSF	69	A	C	C
245/70R17.5	143/141 (146/146)	J (F)	TL	GTL919	3PMSF	69	A	C	C
245/70R19.5	141/140	J	TL	GTL919	3PMSF	69	A	C	C
265/70R19.5	143/141	J	TL	GTL919	3PMSF	69	A	C	C
285/70R19.5	150/148	J	TL	GTL919	3PMSF	69	A	C	C
425/65R22.5	165	K	TL	GTL919	3PMSF	69	A	B	C
435/50R19.5	164	J	TL	GTL925	3PMSF	69	A	D	C
445/45R19.5	164	J	TL	GTL925	3PMSF	69	A	C	B

REGIONAL



Size	LI	SI	Tube Type	Pattern	Noise (dB)	A	B	C	D
9.5R17.5	143/141	K	TL	GAR820	3PMSF	74	B	C	E
205/75R17.5	124/122	M	TL	GAR820	3PMSF	71	A	D	D
215/75R17.5	128/126	M	TL	GAR820	3PMSF	71	A	D	D
225/75R17.5	129/127	M	TL	GAR820	3PMSF	71	A	D	D
235/75R17.5	132/130	M	TL	GAR820	3PMSF	71	A	C	D
245/70R17.5	136/134	M	TL	GAR820	3PMSF	74	B	C	D
205/75R17.5	124/122	M	TL	GDR638	3PMSF	74	B	C	D
215/75R17.5	126/124	M	TL	GDR638	3PMSF	74	B	C	E
225/75R17.5	129/127	M	TL	GDR638	3PMSF	74	B	C	D
235/75R17.5	132/130	M	TL	GDR638	3PMSF	74	B	C	D
245/70R17.5	136/134	M	TL	GDR638	3PMSF	74	B	C	D
245/70R19.5	136/134	M	TL	GDR638	3PMSF	75	B	C	D
265/70R19.5	140/138	M	TL	GDR638	3PMSF	75	B	C	D
285/70R19.5	146/145	M	TL	GDR638	3PMSF	75	B	B	D
10R22.5	144/142	M	TL	GDR688	3PMSF	74	B	C	D
265/70R19.5	143/141	J	TL	GTR923	3PMSF	72	B	C	D

MIXED SERVICE & ON/OFF



Size	LI	SI	Tube Type	Pattern	Noise (dB)	A	B	C	D
13R22.5	156/150 (154/150)	K (L)	TL	GAM831	3PMSF	74	B	B	D
315/80R22.5	158/150 (154/150)	K (L)	TL	GAM831	3PMSF	73	A	B	D
295/80R22.5	154/149 (152/149)	K (L)	TL	GAM837	3PMSF	73	B	C	C
315/70R22.5	156/150 (154/150)	K (L)	TL	GAM837	3PMSF	72	B	C	D
12.00R24	160/156	K	TT	GAM833	M+S	73	B	C	C
325/95R24	162/160	K	TL/TT	GAM833	M+S	73	B	B	C
13R22.5	156/150	K	TT	GDM686+	3PMSF	73	A	B	E
11R22.5	148/145	J	TL	GDM686	3PMSF	73	A	B	E
12R22.5	152/148	K	TL	GDM686	3PMSF	73	A	B	E
13R22.5	156/150	K	TL	GDM686	3PMSF	73	A	B	E
295/80R22.5	152/149	K	TL	GDM686	3PMSF	73	A	B	D
315/80R22.5	158/150	K	TL	GDM686	3PMSF	73	A	B	D
385/65R22.5	164 (158)	K (L)	TL	GAM851	3PMSF	72	B	B	C
425/65R22.5	165	K	TL	GAM851	3PMSF	72	B	B	C
445/65R22.5	169	K	TL	GAM851	3PMSF	72	B	B	C
14.00R20	164/161	J	TL	GAO897		*	*	*	*

* Excluded from EU labelling (POR tire)